

VEHICLE SPECIFICATION		CV JOINT	FRONT SHAFT	REAR SHAFT	DRIVE FLANGE (FRONT)	DRIVE FLANGE (REAR)
<b>DEFENDER 90</b>						
- Up to Turbo Diesel - circa 1989 <b>see note 1</b>		CVE	OSF	OSR	5806	5806
- 200 tdi <b>see note 1</b>	To KA 930455 - <b>see note 6</b>	CVE	OSF	OSR	5806	5806
	From LA 930456	CVL	OSF	NSR	859	859
- 300 tdi/Td5/2.4 Tdci <b>see note 5</b>		CVL	OSF	NSR	859	859
<b>DEFENDER 110</b>						
- Up to Turbo Diesel - circa 1989 <b>see note 1</b>		CVE	OSF	Sal Early	5806	5806
- 200 tdi <b>see note 1</b>	To KA 930455 - <b>see note 6</b>	CVE	OSF	Sal Early	5806	5806
	From LA 930456	CVL	OSF	Sal Late	859	859
- 300 tdi/Td5 <b>see note 2 &amp; 5</b>		OSF	CVL/CV ABS	Sal Late	859	859
- Puma <b>see note 2 &amp; 5</b>		OSF	CVL/CV ABS	NSR	859	859
<b>DISCOVERY I</b>						
- Without ABS (up to VIN JA032850) <b>see note 1 &amp; 3</b>		CVE	OSF	OSR	5806/M	5806/M
- Without ABS (from VIN JA032851) <b>see note 1 &amp; 2</b>		CVL	OSF	NSR	859	859
- With ABS <b>see note 1 &amp; 2</b>		CVABS	OSF	NSR	859	859
<b>DISCOVERY II</b>						
Front kit includes CV joints/halfshafts/boots/clips		DISCO II FRONT KIT		DII REAR	Not applicable	Not applicable
<b>RANGE ROVER CLASSIC</b>						
VIN CA - JA624755 Non ABS, <b>see note 1 &amp; 3</b>		CVE	OSF	OSR	5806/M	5806/M
VIN KA 624756 onwards, Non ABS, <b>see note 1</b>		CVL	OSF	NSR	859	859
Vehicles with ABS - <b>see note 7</b>		CVABS	OSF	NSR	859	859
<b>RANGE ROVER P38</b>						
		Unable to supply	Unable to supply	Unable to supply	Unable to supply	Unable to supply
<p><b>Note 1</b> - If replacing standard stock 10 spline you will also require some form of 24 spline diff centre</p> <p><b>Note 2</b> - Our CV joints can only be fitted with our or other 23 spline shafts. If your rear shafts have integral flanges it will be necessary for you to fit ours (or others) flanges.</p> <p><b>Note 3</b> - To fit our CV joints you will need to purchase Modified Stub Axles (part no. Mod Stubs) &amp; you will need our 5806/M to fit</p> <p><b>Note 4</b> - The standard shafts have intergral flanges and it will be necessary for you to fit our modified flanges</p> <p><b>Note 5</b> - The CV joint ABS style can only be fitted with our range of shafts</p> <p><b>Note 6</b> - If you have a 32 spline at the CV end of the shaft you will have to also fit our front shafts.</p> <p><b>Note 7</b> - You will also require 2 x FTC5268 oil seal.</p>						